

All information is subject to change without notice. Please read bottom notes.


RoHS compatible

- FEATURES :** (1)6.5" VGA color display with High Luminance (550cd/m²)
 (2)Wide Viewing Angle (Vertical:120 degrees, Horizontal:140 degrees)
 (3)Built in Long Life LEDs (MTBF:70,000 h)
 (Condition; Ta=25°C, PWM=100%(continuous lighting))
 (4)Replaceable structure of LED units
 (5) Contain LED driver

TENTATIVE

Specification

Display size	6.5type(17cm)
Number of Pixels	640(W) X 480(H) (VGA)
Display Mode	TFT-LCD (Transmissive type, Normally-White)
Pixel Pitch (mm)	0.207(W) X 0.207(H)
Luminance (typ.)	550 cd/m ²
Response Time (typ.)	T _{ON} =15ms, T _{OFF} =25ms
Contrast	500
Viewing Angle (CR≥10)	Vertical : 120 degrees, Horizontal : 140 degrees
I/F Format & Supply voltage	LVDS RGB 6bit, H/V sync+DE, V _{DD} =3.3V
Operating Temperature	-20 to 70 degrees C.
Outline dimension (mm)	153.0(W) X 121.0(H) X 10.9.(D)mm
Weight (approximately)	250g
Backlight	Sidelight (LEDs)
Power Consumption	3.6W



Rev.0.6R (2009/05/25)

*The information contained herein is presented only as a guide for the applications of our products. No responsibility is assumed by Toshiba Mobile Display Co.,Ltd or other rights of the third parties which may result from its use. No license is granted by implication or otherwise under any patent or patent rights of Toshiba Mobile Display Co.,Ltd or others.

*The information contained herein may be changed without prior notice. It is therefore advisable to contact Toshiba Mobile Display Co.,Ltd before proceeding with the design of equipment incorporating this product.