






ROTATION:
CCW
VIEW FROM:
ODE

UNIT: mm

TOSHIBA RESERVES THE RIGHT TO MAKE CHANGES OF TECHNICAL IMPROVEMENT WITHOUT NOTICE. DO NOT USE FOR CONSTRUCTION, INSTALLATION, OR APPLICATION PURPOSES UNLESS THE DRAWING IS CERTIFIED.

B5-FLANGE MOTOR
DL DRAWING IEC GLOBAL

TYPE: 2-4-6P -
400V
FRAME: 90L

TOLERANCES
X, ±2.0
X.X ±0.5
X.XX ±0.1

3HFN000240

TOSHIBA

TOSHIBA INTERNATIONAL CORPORATION

MAXIMUM
MOTOR WEIGHT

- lbs.
- kgs.

01	Change design BB adding slot hole	T.Danh	20-Apr-18	B.Quynh
NO	REVISION	DRAWN BY	DATE	CHECK

EQP Global SD
XT SERIES

DRAWN BY: HIEN, NGUYEN
CHECK BY: B.X.QUYNH
APPROVED BY: JAY BUGBEE
www.toshiba.com/ind

TOSHIBA INTERNATIONAL CORPORATION Industrial Division / Houston Motor Plant SQUIRREL CAGE INDUCTION MOTOR PERFORMANCE SPECIFICATIONS	INDEX	MPCF-1033
	SHEET NO.	1 of 1
	ISSUED	7/31/13
	SUPERSEDES	11/8/96
	REVISION	2
	WRITTEN BY	MDC
	APPROVED BY	PAA

CUSTOMER: -
TIC SR No.: -

MOTOR NAMEPLATE DATA			
H.P.: -	VOLTS: 230/400	3 PH / 50 Hz	S. RPM: 3000
FRAME: 90L	ENCL: TEFC	FLAMPS: 7.5/4.3	FLRPM: 2885
FORM: FCKL1	S.F.: -	IEC DESIGN N	INSUL CLASS: F
TYPE: IKH	AMB.: 40°C	CODE: -	DUTY: Cont.
MODEL No.: Y222SDMV7JS-PL		kW: 2.2	
NOM. EFF.: 85.9	MIN. EFF.: -	cosØ 0.86	

AMPERAGE	TORQUES	**BEARINGS:
LOCKED ROTOR: 64/37	FULL LOAD (lb-ft.): 5.3	DRIVE END: REFER TO NP
	LOCKED ROTOR (%): 365	OPPOSITE DRIVE END: REFER TO NP
	BREAK DOWN (%): 300	

EFFICIENCY	POWER FACTOR
FULL LOAD: 86.1	FULL LOAD: 86.5
3/4 LOAD: 86.3	3/4 LOAD: 82.2
1/2 LOAD: 84.7	1/2 LOAD: 72.5

ALL CHARACTERISTICS ARE AVERAGE EXPECTED VALUES BASED UPON RATED VOLTAGE, FREQUENCY AND SINEWAVE POWER INPUT. THE DECLARED LOCKED ROTOR CURRENT HAS A TOLERANCE OF 20%. * TEMPERATURE RISE WILL BE CONSISTENT WITH INSULATION, AMBIENT AND SERVICE FACTOR AS DEFINED BY NEMA-MG-12 OR -20. ** BEARINGS ARE THE ONLY RECOMMENDED SPARE PART(S).
--

CERTIFIED BY: Zichao Xie

DATE: 1/7/2020


TOSHIBA INTERNATIONAL CORPORATION

Speed Torque/Current Curve

Model #:	Y222SDMV7JS-PL			FLAmps:	7.5/4.3
Enclosure:	TEFC	Voltage:	230/400 V	Frame:	90L
Pole:	2	Frequency:	3 PH / 50 Hz	Ins. Class:	F
KW:	2.2	Rotor Inertia:	0.09 lb-ft ²	Date:	1/7/2020
FLRPM:	2885	Load Inertia:	N/A	File:	GH2Y22 (2.2kW)

Locked Rotor Amps:	64/37 A	Load Type:	N/A
Locked Rotor Torque:	365%	Starting at:	N/A
Breakdown Torque:	300%	Accel. Time:	N/A
Rated Torque:	5.3 lb-ft		

Design Values



Comments: PROJECT -

D.E.Curve #: GH2Y22 (2.2kW)

Prepared by: Zichao Xie


Checked by:

TOSHIBA INTERNATIONAL CORPORATION

Thermal Limit & Acceleration Curves

Design Values (For Reference Only)

Model #:	Y222SDMV7JS-PL			FLAmps:	7.5/4.3
Enclosure:	TEFC	Voltage:	230/400 V	Frame:	90L
Pole:	2	Frequency:	3 PH / 50 Hz	Ins. Class:	F
KW:	2.2	Rotor Inertia:	0.09 lb-ft ²	Date:	1/7/2020
FLRPM:	2885	Load Inertia:	N/A	File:	GH2Y22 (2.2kW)



Comments: PROJECT -

D.E.Curve #: GH2Y22 (2.2kW)

Prepared by: Zichao Xie

Checked by:

TOSHIBA INTERNATIONAL CORPORATION Industrial Division / Houston Motor Plant SQUIRREL CAGE INDUCTION MOTOR PERFORMANCE SPECIFICATIONS	INDEX	MPCF-1033
	SHEET NO.	1 of 1
	ISSUED	7/31/13
	SUPERSEDES	11/8/96
	REVISION	2
	WRITTEN BY	MDC
	APPROVED BY	PAA

CUSTOMER: -
TIC SR No.: -

MOTOR NAMEPLATE DATA			
H.P.: -	VOLTS: 240/415	3 PH / 50 Hz	S. RPM: 3000
FRAME: 90L	ENCL: TEFC	FLAMPS: 7.4/4.3	FLRPM: 2885
FORM: FCKL1	S.F.: -	IEC DESIGN N	INSUL CLASS: F
TYPE: IKH	AMB.: 40°C	CODE: -	DUTY: Cont.
MODEL No.: Y222SDMV7JS-PL		kW: 2.2	
NOM. EFF.: 85.9	MIN. EFF.: -	cosØ 0.83	

AMPERAGE	TORQUES	**BEARINGS:
LOCKED ROTOR: 66/38	FULL LOAD (lb-ft.): 5.3	DRIVE END: REFER TO NP
	LOCKED ROTOR (%): 450	OPPOSITE DRIVE END: REFER TO NP
	BREAK DOWN (%): 320	

EFFICIENCY	POWER FACTOR
FULL LOAD: 86.0	FULL LOAD: 83.1
3/4 LOAD: 85.9	3/4 LOAD: 77.4
1/2 LOAD: 83.8	1/2 LOAD: 66.1

ALL CHARACTERISTICS ARE AVERAGE EXPECTED VALUES BASED UPON RATED VOLTAGE, FREQUENCY AND SINEWAVE POWER INPUT. THE DECLARED LOCKED ROTOR CURRENT HAS A TOLERANCE OF 20%. * TEMPERATURE RISE WILL BE CONSISTENT WITH INSULATION, AMBIENT AND SERVICE FACTOR AS DEFINED BY NEMA-MG-12 OR -20. ** BEARINGS ARE THE ONLY RECOMMENDED SPARE PART(S).
--

CERTIFIED BY: Zichao Xie

DATE: 12/27/2019


TOSHIBA INTERNATIONAL CORPORATION

Speed Torque/Current Curve

Model #:	Y222SDMV7JS-PL			FLAmps:	7.4/4.3
Enclosure:	TEFC	Voltage:	240/415 V	Frame:	90L
Pole:	2	Frequency:	3 PH / 50 Hz	Ins. Class:	F
KW:	2.2	Rotor Inertia:	0.09 lb-ft ²	Date:	12/27/2019
FLRPM:	2885	Load Inertia:	N/A	File:	GH2Y22 (2.2kW)

Locked Rotor Amps:	66/38 A	Load Type:	N/A
Locked Rotor Torque:	450%	Starting at:	N/A
Breakdown Torque:	320%	Accel. Time:	N/A
Rated Torque:	5.3 lb-ft		

Design Values



Comments: PROJECT -

D.E.Curve #: GH2Y22 (2.2kW)

Prepared by: Zichao Xie


Checked by:

TOSHIBA INTERNATIONAL CORPORATION

Thermal Limit & Acceleration Curves

Design Values (For Reference Only)

Model #:	Y222SDMV7JS-PL			FLAmps:	7.4/4.3
Enclosure:	TEFC	Voltage:	240/415 V	Frame:	90L
Pole:	2	Frequency:	3 PH / 50 Hz	Ins. Class:	F
KW:	2.2	Rotor Inertia:	0.09 lb-ft ²	Date:	12/27/2019
FLRPM:	2885	Load Inertia:	N/A	File:	GH2Y22 (2.2kW)



Comments: PROJECT -

D.E.Curve #: GH2Y22 (2.2kW)

Prepared by: Zichao Xie

Checked by:

TOSHIBA INTERNATIONAL CORPORATION Industrial Division / Houston Motor Plant SQUIRREL CAGE INDUCTION MOTOR PERFORMANCE SPECIFICATIONS	INDEX	MPCF-1033
	SHEET NO.	1 of 1
	ISSUED	7/31/13
	SUPERSEDES	11/8/96
	REVISION	2
	WRITTEN BY	MDC
	APPROVED BY	PAA

CUSTOMER: -
TIC SR No.: -

MOTOR NAMEPLATE DATA			
H.P.: -	VOLTS: 220/380	3 PH / 50 Hz	S. RPM: 3000
FRAME: 90L	ENCL: TEFC	FLAMPS: 7.8/4.5	FLRPM: 2865
FORM: FCKL1	S.F.: -	IEC DESIGN N	INSUL CLASS: F
TYPE: IKH	AMB.: 40°C	CODE: -	DUTY: Cont.
MODEL No.: Y222SDMV7JS-PL		kW: 2.2	
NOM. EFF.: 85.9	MIN. EFF.: -	cosØ 0.88	

AMPERAGE	TORQUES	**BEARINGS:
LOCKED ROTOR: 61/35	FULL LOAD (lb-ft.): 5.3	DRIVE END: REFER TO NP
	LOCKED ROTOR (%): 365	OPPOSITE DRIVE END: REFER TO NP
	BREAK DOWN (%): 270	

EFFICIENCY	POWER FACTOR
FULL LOAD: 84.7	FULL LOAD: 88.4
3/4 LOAD: 85.4	3/4 LOAD: 85.3
1/2 LOAD: 84.4	1/2 LOAD: 77.6

ALL CHARACTERISTICS ARE AVERAGE EXPECTED VALUES BASED UPON RATED VOLTAGE, FREQUENCY AND SINEWAVE POWER INPUT. THE DECLARED LOCKED ROTOR CURRENT HAS A TOLERANCE OF 20%. * TEMPERATURE RISE WILL BE CONSISTENT WITH INSULATION, AMBIENT AND SERVICE FACTOR AS DEFINED BY NEMA-MG-12 OR -20. ** BEARINGS ARE THE ONLY RECOMMENDED SPARE PART(S).
--

CERTIFIED BY: Zichao Xie

DATE: 1/7/2020


TOSHIBA INTERNATIONAL CORPORATION

Speed Torque/Current Curve

Model #:	Y222SDMV7JS-PL			FLAmps:	7.8/4.5
Enclosure:	TEFC	Voltage:	220/380 V	Frame:	90L
Pole:	2	Frequency:	3 PH / 50 Hz	Ins. Class:	F
KW:	2.2	Rotor Inertia:	0.09 lb-ft ²	Date:	1/7/2020
FLRPM:	2865	Load Inertia:	N/A	File:	GH2Y22 (2.2kW)

Locked Rotor Amps:	61/35 A	Load Type:	N/A
Locked Rotor Torque:	365%	Starting at:	N/A
Breakdown Torque:	270%	Accel. Time:	N/A
Rated Torque:	5.3 lb-ft		

Design Values



Comments: PROJECT -

D.E.Curve #: GH2Y22 (2.2kW)

Prepared by: Zichao Xie


Checked by:

TOSHIBA INTERNATIONAL CORPORATION

Thermal Limit & Acceleration Curves

Design Values (For Reference Only)

Model #:	Y222SDMV7JS-PL			FLAmps:	7.8/4.5
Enclosure:	TEFC	Voltage:	220/380 V	Frame:	90L
Pole:	2	Frequency:	3 PH / 50 Hz	Ins. Class:	F
KW:	2.2	Rotor Inertia:	0.09 lb-ft ²	Date:	1/7/2020
FLRPM:	2865	Load Inertia:	N/A	File:	GH2Y22 (2.2kW)



Comments: PROJECT -

D.E.Curve #: GH2Y22 (2.2kW)

Prepared by: Zichao Xie

Checked by:

TOSHIBA INTERNATIONAL CORPORATION Industrial Division / Houston Motor Plant SQUIRREL CAGE INDUCTION MOTOR PERFORMANCE SPECIFICATIONS	INDEX	MPCF-1033
	SHEET NO.	1 of 1
	ISSUED	7/31/13
	SUPERSEDES	11/8/96
	REVISION	2
	WRITTEN BY	MDC
	APPROVED BY	PAA

CUSTOMER: -
TIC SR No.: -

MOTOR NAMEPLATE DATA			
H.P.: 3	VOLTS: 460	3 PH / 60 Hz	S. RPM: 3600
FRAME: 90L	ENCL: TEFC	FLAMPS: 3.7	FLRPM: 3505
FORM: FCKL1	S.F.: 1.15	NEMA DESIGN: A	INSUL CLASS: F
TYPE: IKH	AMB.: 40°C	CODE: M	DUTY: Cont.
MODEL No.: Y222SDMV7JS-PL		kW: 2.2	
NOM. EFF.: 86.5	MIN. EFF.: -	P.F.: 85.0	

AMPERAGE	TORQUES	**BEARINGS:
LOCKED ROTOR: 39	FULL LOAD (lb-ft.): 4.3	DRIVE END: REFER TO NP
	LOCKED ROTOR (%): 420	OPPOSITE DRIVE END: REFER TO NP
	BREAK DOWN (%): 335	

EFFICIENCY	POWER FACTOR
FULL LOAD: 88.1	FULL LOAD: 85.3
3/4 LOAD: 87.6	3/4 LOAD: 80.9
1/2 LOAD: 85.3	1/2 LOAD: 71.3

ALL CHARACTERISTICS ARE AVERAGE EXPECTED VALUES BASED UPON RATED VOLTAGE, FREQUENCY AND SINEWAVE POWER INPUT. THE DECLARED LOCKED ROTOR CURRENT HAS A TOLERANCE OF 20%. * TEMPERATURE RISE WILL BE CONSISTENT WITH INSULATION, AMBIENT AND SERVICE FACTOR AS DEFINED BY NEMA-MG-12 OR -20. ** BEARINGS ARE THE ONLY RECOMMENDED SPARE PART(S).
--

CERTIFIED BY: Zichao Xie

DATE: 1/7/2020


TOSHIBA INTERNATIONAL CORPORATION

Speed Torque/Current Curve

Model #:	Y222SDMV7JS-PL			FLAmps:	3.7
Enclosure:	TEFC	Voltage:	460 V	Frame:	90L
Pole:	2	Frequency:	3 PH / 60 Hz	Ins. Class:	F
HP:	3	Rotor Inertia:	0.09 lb-ft ²	Date:	1/7/2020
FLRPM:	3505	Load Inertia:	N/A	File:	GH2Y22 (2.2kW)

Locked Rotor Amps:	39 A	Load Type:	N/A
Locked Rotor Torque:	420%	Starting at:	N/A
Breakdown Torque:	335%	Accel. Time:	N/A
Rated Torque:	4.3 lb-ft		

Design Values



Comments: PROJECT -

D.E.Curve #: GH2Y22 (2.2kW)

Prepared by: Zichao Xie


Checked by:

TOSHIBA INTERNATIONAL CORPORATION

Thermal Limit & Acceleration Curves

Design Values (For Reference Only)

Model #:	Y222SDMV7JS-PL			FLAmps:	3.7
Enclosure:	TEFC	Voltage:	460 V	Frame:	90L
Pole:	2	Frequency:	3 PH / 60 Hz	Ins. Class:	F
HP:	3	Rotor Inertia:	0.09 lb-ft ²	Date:	1/7/2020
FLRPM:	3505	Load Inertia:	N/A	File:	GH2Y22 (2.2kW)



Comments: PROJECT -

D.E.Curve #: GH2Y22 (2.2kW)

Prepared by: Zichao Xie

Checked by: